


| FIXTURE NUMBER JOB TITLE | : |
|--------------------------|---|
| | |
| | : |
| | : |
| | : |
| APPROVED BY DATE | |



CONSTRUCTION

The housing is corrosion free 30% glass-filled high impact resistant thermoset polyester making it ideal for high temperatures. The guard is manufactured in a high impact resistant glass reinforced polymer alloy. All screws are stainless steel. All inserts are brass. Inserts are ultrasonically welded into the housing. Gaskets are long life silicone.

COLORS

MAXIMUM AMBIENT OPERATING TEMPERATURE

Gray, Black, White, Red, Blue, Green, and Yellow. 10

104°F



PENDANT MOUNT

LED INFO

DRIVER INFO

Luminaire power = 19.2W Color Temp = 4000K CRI = 82 Total Light Output = 1832 lumens Efficacy = 95.4 lumens/watt Type = Constant current
Dimming Driver = 0-10v

120v = .972A / 277v = .926A

Max THD 15.69% at 277v

Standard drivers are programmable to match wattage or lumen requirements.

INSTALLATION

The ceiling box has four ¾" threaded hubs with liquid tight knockouts. Internal grounding system allows for hub to hub grounding continuity when using metallic wiring methods (lock nuts are required). Two mounting feet are spaced at 5¼". Pendant mount fixtures have a single ¾" threaded hub with a locking set screw. Use minimum 90°C rated lead wires. Guard equipped with set screw for locking.



Meets Buy American Act, IP66, NEMA 4X, CSA certified, C22.2 No. 250.0-08 Luminaires, Conforms to UL 1598, 3rd Ed. 2008, CSA C22.2 No. 250.13-12, Conforms to UL 8750, 1st Ed.



| Color | Wattage | Lamps | Mounting | Fixture Type | Guard | Globe Options |
|--|-------------------|--------|---|--------------|----------------|---|
| 01: White 02: Gray 03:: Black 04: Red 05: Blue 06:Green 07: Yellow | 12W 15W 20W | L: LED | C: Ceiling Mount W: Wall Mount P: Pendant Mount | F: With Box | OG: Guard Only | 01 - Standard Opal Glass 09 - Standard Clear Glass 18 - Frosted Glass 29 - Prismatic Clear Glass * Colored globes may be available upon request ** Polycarbonate globes not available |



MORE INFORMATION Call 800.441.1771 or email us at ostin@canlet.com & COST ESTIMATES www.Canlet.com